

455

BLOW HOLE REPAIR (Syringe)

GENERAL DESCRIPTION

The Emecole Metro 455 syringe is designated for use as a blow hole repair material, following the application of Emecole Metro Surface Seal material. It has outstanding cured strength and is not recommended when removal is required.

TECHNICAL DATA

	<u>Prepolymer</u>	<u>Curative</u>
Viscosity (cps)	15000	20-40000
Ratio by weight	1.08	1.00
Ratio by volume	1	1
Color	White	Gray
	<u>Mixed</u>	
Nominal working time	5-8 minutes	
Nominal injection time	10-20 minutes	

CLEAN UP

In general, should be a moisture-free solvent. Most effective is methylene chloride, followed by MIBK. If above is not acceptable, use less efficient solvents such as mineral spirits or DOP.

WARRANTY

Recommendations concerning the performance or use of this product are based upon independent test reports believed to be reliable. If the product is proven to be defective, at the option of the Manufacturer, it will be either replaced or the purchase price refunded. The Manufacturer will not be liable in excess of the purchase price. The user will be responsible for deciding if the product is suitable for his application and will assume all risk associated with the use of the product. This warranty is in lieu of any other warranty expressed or implied, including but not limited to an implied warranty of merchantability or an implied warranty of fitness for a particular use.